

3Gb SAS-SAS/SATA-II RAID E5412E

IT executives require significantly improved data storage infrastructure solutions for application and database archiving, e-mail, tiered storage, virtual tape libraries, and advanced data protection solutions. Addressing regulatory requirements, legal mandates, and improving disaster recovery along with much greater data storage power and volumetric efficiency have become critical success factors.

OEMs delivering solutions to meet these needs are also under pressure to address four key challenges: shorten time to market; reduce test, integration, warranty, and service costs; increase reliability; and bolster customer satisfaction. Xyratex RAID solutions reduce OEM development costs, feature enterprise-class RAID functionality including RAID 6 and Snapshot, ensure high availability, and they are highly reliable.

• Enhance Applications with Storage: Xyratex E5412E

The E5412E combines Serial Attached SCSI (SAS) connectivity with SAS (SAS) and Serial ATA (SATA) drive technology for cost effective, high performance storage solutions. It combines high performance connectivity, sophisticated storage management software, flexible interface support, and highly reliable storage devices to deliver a cost-effective, ultra-high performance OEM solution with the scalability and functionality necessary to meet the demands of today as well as tomorrow's rigorous applications environment. By leveraging the SAS full duplex, point-to-point architecture with dedicated connections, the E5412E delivers maximum data throughput, thereby providing faster, more responsive applications. In addition, the E5412E sustains maximum throughput (MB/s) for high bandwidth applications ranging from video editing to database-intensive online transaction processing.

Meanwhile, SATA-II drives in the E5412E provide the combination of high-capacity and cost-effective data storage normally found in nearline storage. Using SATA disks with their low cost-per-gigabyte design, the E5412E provides a cost-effective online repository for non-business-critical data, and offers the many advantages of tiered storage to the Small and Medium Business (SMB) market. Xyratex E5412E sets new standards for entry-level RAID storage offerings.

• Managing Storage From A Single Pane of Glass

All models in the Xyratex 5000 RAID series come with Snapshot. Four snapshots are available to start implementing point-in-time recovery capabilities. An optional Snapshot upgrade allows for up to 24 snapshots per Logical Drive and up to 512 total snapshots per RAID system.

Xyratex's StorView software configures and administers the E5412E storage system, and distinguishes it from other entry-level systems on the market today. Automated control of individual controller's cache, arrays and devices via a web-based interface simplifies storage administration, while StorView's full-function Command Line Interface (CLI) allows integration of array management into existing operational procedures. An optional upgrade to StorView Global Manager enables configuration, monitoring and management of any 5000 Series RAID controller from any location, anywhere on the network. The StorView software also enables access to the RAID Advanced Power Management which can be used to reduce the operational costs of the RAID storage system, while ensuring continuous availability to data.



Features

- Single (2) or Dual (4) 3Gb/s 4-lane SAS host connections per system
- Mix up to 60 high performance SAS and cost effective SATA-II drives
- Snapshot support for up to 512 snaps
- StorView™ controller based management software
- Full RAID 6 & Snapshot support
- Dual active high availability and low cost single controller configurations
- Host based dynamic multi-pathing for high availability
- Online capacity growth through dynamic array and LUN expansion
- Redundant modular design with hot-swappable components
- RAID Advanced Power Management

x y r a t e x •

3Gb SAS-SAS/SATA-II RAID E5412E

• Technical Specification

General Information

Product Code	RS-1220-E3-5412E
External Interface	3Gb 4-lane SAS connection
Supported Operating Platforms	Windows 2003 (IA32, EM64T, IA64); RedHat Linux AS3/AS4 (IA32, EM64T, IA64); SuSE Linux 9/10 (IA32, EM64T, IA64)
Supported Hosts	256, 512 LUNs, LUN Masking, >2TB LUNs
Expansion Chassis	RS-1220-E3-XPN (4 max), SAS connected (SFF-8470), single & dual IO module configs
Total Expansion Capacity	60TB, 1GB cache per controller (selectable by volume: read, adaptive read-ahead, write through, write-back), battery backup

Disk Drives

Disk Drives Supported	For a full list of supported drives, please contact your account or sales manager
Interface Types Supported	SAS (3Gb), SATA-II (3Gb), NCQ, dedicated bandwidth to each drive
Max Drives per Enclosure	12, 512 Logical Drives/system, automatic bad sector assignment

RAID Controllers

No. RAID Controllers	1 (single) or 2 (dual – HA)
RAID Levels Supported	Up to 60 disk arrays with independent RAID level 0, 1, 5, 6, 10, and 50 support, selectable strip sizes (64, 128, & 256K)
RAID Protection Features	Background initialization, background parity checking, and automatic drive rebuild with redundant RAID arrays

System Management

Software	StorView, StorView Global, StorView Path Manager
Interfaces Supported	Ethernet (out-of-band), FC host based (in-band), Xyratex Command Line Interface (CLI) for RAID

System Availability

Hot Swappable Components	Disk drives, RAID controllers, power supplies and cooling module
Additional Reliability Features	StorView Path Manager – Windows host based dynamic multi-path failover

Dimensions

Height	87.9mm (3.46") 2 EIA units
Width	443.7mm (17.49") IEC rack compliant
Depth	550mm (21.65")
Weight	32.2Kg (71 lbs) dual controller configuration with drives

Electrical: AC Input

Voltage	100 to 240 V AC @ 50/60Hz Single Phase
Input Current	6.0A (115V AC), 3.0A (230V AC)
Input Power	300W Typical

Environmental: Operating

Temperature	5°C to 40°C (41°F to 104°F)
Humidity	8% to 80% non-condensing
Altitude	0 to 2,133m (0 to 7,000')
Shock	5g 10ms ½ sine
Vibration	Random 0.21g 5-500Hz
Acoustics	<58dB LpA @20°C

Environmental: Non-Operating

Temperature	1°C to 50°C (33.8°F to 122°F)
Humidity	8% to 80% non-condensing
Altitude	0 to 12,192m (0 to 40,000')
Shock	30g 10ms ½ sine
Vibration	Random 1.04g 2-200Hz

Approvals

CCC, BSMI, CE, UL, cUL, RoHS (R5), Microsoft WHQL, Microsoft RAID System Submission – MPIO (2-Node Cluster)

Warranty Information

Enclosures with drives Up to 3 years. Please contact Xyratex for detailed warranty information.

Environmental Standards



ISO 14001: 2004 Cert No. EMS91560



USA Sales & Support

T +1 877 997 2839
T +1 877 XYRATEx

UK HQ

T +44(0)23 9249 6000
F +44(0)23 9245 3654

©2008 Xyratex (The trading name of Xyratex Technology Limited). Registered in England & Wales. Company no: 03134912. Registered Office: Langstone Road, Havant, Hampshire PO9 1SA, England. The information given in this brochure is for marketing purposes and is not intended to be a specification nor to provide the basis for a warranty. The products and their details are subject to change. For a detailed specification or if you need to meet a specific requirement please contact Xyratex: www.xyratex.com.